




A thd. Spl. Acme	D dia.	G	L	M	S hex	V thread
5/8 - 6	.812	.125	.656	.593	.750	11/16-24NEF-2A



STANDARD DATA	
Shell Material	Aluminum Alloy
Shell Finish	Cadmium plate with olive drab chromate conversion coating
Insulation	Polychloroprene
Contact Termination	Solder
Contact Material	Copper Alloy
Contact Finish	Gold over suitable underplate
Number of Contacts	6
Coupling Method	Special Acme thread coupling nut.
Contact Rating	#20—5 amps

**BX Subminiature**  
Face view of pin insert



SHELL SIZE & ARR. No. 10-6  
 CONTACT SIZE 6 #20  
 SERVICE RATING 1  
 Equivalent to: MC14E10-6SN

**BRANDEX COMPONENTS, INC**

10440 N.W. 50TH STREET, SUNRISE FL, 33351  
 PHONE: 954 746-4669

TITLE

**STRAIGHT RECEPTACLE  
 10-6**

SIZE <b>A</b>	FSCM <b>04NT4</b>	DRAWING NO. <b>BX14E10-6SN</b>	REV. <b>B</b>
------------------	----------------------	-----------------------------------	------------------

DATE 02/12/03	SCALE NOT SCALE DRAWING	SHEET 1 of 1
------------------	----------------------------	-----------------